

Adjustable Stock Support Online Extra

Dec/Jan 2011, Issue 38, Page 62

Adjustable Stock Support Cut List

| | Part | Thickness | Width | Length | Qty. | Mat'l |
|----|---------------|-----------|-------------|---------|------|-------|
| A | Front foot | 1" | 3" | 20" | 1 | M |
| B | Front leg | 3/4" | 2 3/4" | 24 1/2" | 1 | M |
| C | Housing sides | 3/4" | 1 1/2" | 21 1/2" | 2 | M |
| D* | Brackets | 3/4" | 1" | 4 1/4" | 2 | M |
| E | Housing cover | 3/4" | 4 1/4" | 12" | 1 | M |
| F* | Back foot | 1" | 1" | 10" | 1 | M |
| G | Back leg | 3/4" | 3 1/2" | 26" | 1 | M |
| H | Sliding arm | 3/4" | 2 3/4" | 24 1/2" | 1 | M |
| I | Head | 1" | 3" | 18" | 1 | M |
| J | Head plugs | 3/4" | 1 3/4" dia. | | 2 | M |
| K | Lock block | 3/4" | 2" | 2" | 1 | M |
| L | Knob | 3/4" | 2" dia. | | 1 | M |

*Part/s are cut out of other project parts. See instructions.

Materials: M=Maple **Hardware/Supplies:** (1) 1/4" x 24" steel rod; (1) 3/4" x 24" threaded rod; (2) 3/4" T-nuts; (4) 3/4" nuts; (2) 1/4" nuts; (2) 1 1/2 x 12" PVC pipe (schedule 40); (1) brass chain, 8" long; (2) 1 1/8" screw eyes; (4) #8 x 1 3/8" flathead wood screws; (1) 1"-dia. dowel, 3/4" long; (1) 1/4"-dia. dowel pin, 1" long

